

H.A.B Model S 225 – 24 D4WDS

Features:



- Driveable in full height
- Foldable steel guard rails
- CE – certified components
- Automatic self-levelling outrigger system
- 4WD
- Max. stability due to three – scissors mechanism
- Unlimited platform capacity on platform and extension
- All proportional drive, lift and lowering functions

Technical Features

Working height	22.50 m
Platform height	20.50 m
Platform size	4.50 m x 2.36 m
Lateral platform extension	2.70 m
Clearance height	2.88 m – 3.72 m
Platform capacity	750 kg
Outer turning radius	5.50 m
Inner turning radius	3.50 m
Battery capacity	Deutz 29 KW
Drive speed in km/h (l/e) *	4.5 0.7
Diesel	Yes
Lifting time	58 Sec
Lowering time	60 Sec
Ground clearance	350 mm
Wheelbase	3.20 m
Max. inclination	3°
Control	Proportional
Gradeability	ca. 40%
Weight	11000 kg
Max. ground bearing pressure	57N/cm ²
Driveable in full height	Yes
External using	Yes
4 WD	Yes
4 WS	No
Self-levelling Jacks	Yes
Transport Features	
Hight	2.88 m
Lenght	4.84 m
Width	2.39 m

*e=elevated; l=lowered

Subject to change without prior notice.



H.A.B.

H.A.B. Service Center GmbH
Heidigstrasse 17
76709 Kronau

Telefon: +49 (0) 7253 / 94 01 – 0
Telefax: +49 (0) 7253 / 94 01 – 26
service@hab-hubarbeitsbuehnen.de