



|          |          |            |         |         |         |         |         |
|----------|----------|------------|---------|---------|---------|---------|---------|
| 230 kg   | 120 kg   | 120/230 kg | L1      | L2      | W1      | W2      | W3      |
| 12000 mm | 13000 mm | 8000 mm    | 5091 mm | 6469 mm | 4583 mm | 3661 mm | 2744 mm |

BI-ENERGY  
Diesel+AC



TSJ 30.1/C 30 m 13 m 230 kg 175° 540° 180x70 cm 90°+80° 5-2,86 m 26% 40% 1,7 km/h 4650 kg 29 kN 2,30 kN/m<sup>2</sup> 3,72 kN/m<sup>2</sup> 980/1300 mm 6650 mm 1990 mm

TSJ 30.1/R 30 m 13 m 230 kg 175° 540° 180x70 cm 90°+80° 5-2,86 m 26% 25% 1,3 km/h 4840 kg 29 kN 2,40 kN/m<sup>2</sup> 3,81 kN/m<sup>2</sup> 980 mm 6760 mm 1780 mm



Battery type



Battery charge



Add. Weight



Autonomy



Charging time

Electropump

|        |           |  |                |              |        |               |    |            |
|--------|-----------|--|----------------|--------------|--------|---------------|----|------------|
| ECO    | DC+AC     |  | 48V 320 A/h 5h | 230V-48V 45A | 450 kg | 6-7 h endless | 7h | 48V 12 kW  |
| ECO    | DC+AC     |  | 48V 270 A/h 5h | 230V-48V 45A | 400 kg | 6-7 h endless | 7h | 48V 9 kW   |
| HYBRID | Diesel+DC |  | 24V 240 A/h 5h | 230V-24V 35A | 200 kg | 2-3 h endless | 7h | 24V 5,5 kW |

Characteristics and technical data are informative only and subjected to change without notice.